



### Description

Mircom's Continental Series Lobby Panels are designed to provide Resident/Visitor access control for buildings such as apartments, multi-dwellings, condominiums and offices.

The Continental Series Lobby Panels are available in a hands-free (MCS-6001S) or a handset (MCS-6001SH) version. The Continental Series and its accessories are primarily designed for an indoor environment. The stainless steel construction enhances the aesthetics of any entrance lobby or gateway where they are located. The panels can be either surface or flush mounted.

The systems comes complete with a scrolling directory 4 line by 20 character back-lit LCD display which provide clear messages. In addition these units have provisions for a postal lock switch and a camera to be installed. For extremely cold climates, the TH-102 Heater Kit is recommended with these panels.

The Continental Series Lobby Panels feature telephone controllers for 60, 120 and 360 resident names. (Please refer to the ordering information.)

### Features

- 4 line by 20 character LCD back-lit display
- DIP switch selectable for either AutoDialer or NSL (No Subscriber Line) systems
- Field programmable via the keypad
- Multiple entrance capabilities
- Flexible one to four digit resident codes
- Keyless Entry Codes
- Tone or Pulse compatible
- User Event Tracking for visitors and keyless entry
- Connection for "Lock Back" door contact to prevent "tailgating"
- Built-in Real Time Clock
- Elevator restriction capability
- RS-485 Interface to network to other units
- Postal lock provision
- Option for the Mircom CAM-1 Camera
- Exclusive Distinct Suite Telephone Ring Pattern (NSL only)
- Multiple Speech Paths (NSL only)
- Industry Canada and F.C.C. approved

All controllers are dip switch selectable for either the AutoDialer system, which uses a dedicated phone line to dial preprogrammed telephone numbers when the unique directory code is entered, or the No Subscriber Line system, which does not require a dedicated phone line.

The AutoDialer systems require a dedicated phone line while the NSL systems require other hardware components such as relay cards and relay cabinets. (Please refer to the ordering information.) The system is programmable via its integrated metal keypad or using a computer with the optional MirSoft TAS software and the MDM-1000 Modem Module.

## Operation

The Electronic Directory Lobby Panels allows for duplex communications by permitting a visitor to enter a resident code at the entrance panel which causes the resident's phone to annunciate that a visitor is present. The resident can use their own phone to establish

communication with the visitor. If the resident desires the visitor to enter, they can dial "9" which causes the entrance door to open for a predetermined time. If entry is not desired, then access can be refused by simply hanging up.

## Dimensions

### MCS-6001S

15 3/4" H x 13 7/8" W

### BBF-6001

13 13/16" H x 11 1/4" W x 2 3/16" D

### MCS-6001SH

15 3/4" H x 13 7/8" W

### BBS-6003

15 9/16" H x 13 11/16" W x 2 3/16" D

## Ordering Information

### MODEL NO. DESCRIPTION

#### Lobby Panels

MCS-6001S	Hands-free Continental Series Lobby Panel c/w 4 line by 20 character scrolling directory LCD Display
MCS-6001S	Handset Continental Series Lobby Panel c/w 4 line by 20 character scrolling directory LCD Display
BBF-6001	Flush Mounting Backbox for the Continental Series Lobby Panels
BBS-6003	Surface Mounting Backbox for the Continental Series Lobby Panels

#### Telephone Controllers

2001-0060S	Scrolling Directory Telephone Controller for 60 Resident Names
2001-0120S	Scrolling Directory Telephone Controller for 120 Resident Names
2001-0360S	Scrolling Directory Telephone Controller for 360 Resident Names
2001-0800S	Scrolling Directory Telephone Controller for 800 Resident Names
2001-2000S	Scrolling Directory Telephone Controller for 2000 Resident Names

#### NSL Components

2008M	Master NSL Relay Cabinet. Supports eight 2012 Telephone Line Relay Cards. Includes two PS-24 (Canada)/PS-24P (USA) Transformers.
2008	8 Relay Card Expander Cabinet
2016	16 Relay Card Expander Cabinet
2012	12 Unit Telephone Line Relay Card
9106	6 ft. Relay Cable (one required per 2012 Telephone Line Relay Card)
9106BC	6 ft. Relay Cable for B.C.
2008E	Elevator Restriction Relay Cabinet. Supports eight 2012E Elevator Restriction Relay Cards. Includes one PS-24 (Canada)/PS-24P (USA) Transformer.
2012E	12 Unit Elevator Restriction Relay Cards

#### Accessories

TH-102	Thermostat Heater kit for Slim Line Lobby Panels. Requires separate 24 VAC power source (PS-3B/PS-3P)
USFT-2000	Semi-flush trim ring
CAM-1	Board Camera c/w power supply
PS-24	Transformer 24 VAC/40VA (PS-24P for USA version)
PS-3B	Transformer 8VAC/13VA, 16VAC/17VA, 24VAC/20VA (PS-3P for USA version)
PS-4	Transformer 16VAC/40 VA (PS-4P for USA version)
MDM-1000	Modem Module
M-10	Door Strike 8-12 VAC
MSW-003	MirSoft TAS 2000
RS-485IMA	Interface Module

NOT TO BE USED FOR INSTALLATION PURPOSES.



#### Canada

25 Interchange Way  
Vaughan, Ontario L4K 5W3  
Telephone: (905) 660-4655  
Fax: (905) 660-4113

#### U.S.A.

4575 Witmer Industrial Estates  
Niagara Falls, NY 14305  
Toll Free: (888) 660-4655  
Fax Toll Free: (888) 660-4113

Distributed by:

